



公差/General		公差/General (mm)											公差/General
0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
11	Abnormity Nut	Copper alloy	Ni Plated
10	Adjusting Bolt	Copper alloy	Ni Plated
9	Slip Component	Steel	Zn Plated
8	Bar Copper	Copper alloy	Ni Plated
7	Current Carrier	Copper	Sn Plated
6	Securing Fitting	Copper alloy	Ni Plated
5	Cage	Copper alloy	Ni Plated
4	Screw2	Copper alloy	Ni Plated
3	Screw1	Copper alloy	Ni Plated
2	Housing2	PA66	UL94V-0
1	Housing1	Copper alloy	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				
4				

MATERIAL:	SURFACE:
MAT NO.:	
STATUS:	
APPD: Li GL 2020.05.26	NAME:
CHKD: Mgo J 2020.05.26	PCDK2.5-PE-01P-1Y-00A(H)
DRAFT:Wgng LX 2020.05.26	DRAWING NO.: PCDK 2.5-PE-C01
SIZE: A4	TYPE: CUSTOMER DRAWING
SCALE: 1:1	SCALE: 1:1
	REV
	T0
	1/1

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6.0	/	/
线径扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.5/4.43	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.2~2.5/24~12	/	/
间距/Pitch(mm)	5.20	/	/
剥线长度/Stripping length(mm)	7~8	/	/
使用温度范围/Operating Temperature(°C)	-40~+105	/	/
符合RoHS要求/Conform to RoHS	Yes	/	/
标准颜色编号/Standard color number:		/	/
PANTONE / RAL		/	/

DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD  
宁波高松电子有限公司

PCDK2.5-PE-01P-1Y-00A(H)