



标注公差/General tolerances(mm)		公差带/General Tolerance	
0	>3	>6	>180
~	>10	~	~
3	6	10	30
±0.12	±0.18	±0.22	±0.26
±0.31	±0.37	±0.57	±0.80
±1.09	±1.15	±1.50	±2.20
±2.50	±2.50	±2.50	±2.50

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/15	/	300/10
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	/	320/20
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	/	4
可距/Pitch(mm)/线数范围/Poles	5.08/N=02~24P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环境要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	PANTONE / RAL		

ITEM	NAME OF PART	MATERIAL	NOTES
3	Clamp	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

MATERIAL:	/	SURFACE:	/
MAT NO.:	/	NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/	2EDGA-5.08-XXP-14-00A(H)	
APPD:	LJGL 2020.06.22	NAME:	2EDGA-5.08-001
CHKD:	MGOJ 2020.06.22	DRAWING NO.:	2EDGA-5.08-001
DRFT:	WangY2 2020.06.22	TYPE:	CUSTOMER DRAWING

REV	ECN	DESCRIPTION	DRFT	DATE	SIZE	SCALE	SHEET
1					A4	2:1	1/1