



未注公差/General tolerances(mm)													0.1/10	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400		>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2'

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300V/28	300/28	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	500/32	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6.0	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm ²)	24~10 / 0.2~4&6(SoL)		
间距/Pitch(mm)/线数范围/Poles	6.2/N=01P		
剥线长度/Stripping length(mm)	11~13		
使用温度范围/Operating temperature(°C)	-40~+105		
符合 RoHS 环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number: PANTONE / RAL	/		

ITEM	NAME OF PART	MATERIAL	NOTES
5	Current Carrier 2	Copper	Sn Plated
4	Current Carrier 1	Copper	Sn Plated
3	Spring	Stainless Steel	/
2	Button	PA66+GF%	UL94V-0
1	Housing	PA66	UL94V-0

		MATERIAL: /	SURFACE: /	
		MAT NO./REV: /	MAT STATUS: /	
APPD: Li GL	2022.06.14	NAME		
CHKD: Ma EK	2022.06.14	DRAWING NO. / TYPE CUSTOMER DRAWING / DRAWING STATUS / SCALE 2:1 SHEET 1/1		
DRFT: Zheng QG	2022.06.14			
		DRAWING NO. / TYPE CUSTOMER DRAWING / DRAWING STATUS / SCALE 2:1 SHEET 1/1		

REV	ECN	DESCRIPTION	DRFT	DATE
00	/	/	Zheng QG	2022.06.14

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless express authorization is granted. DEGSON will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 非经书面授权, 否则禁止转让、复制、利用、交还本文件的内容, 一经发现, 立即保留追究法律责任, 本公司保留对涉及发明、实用新型和外观设计的所有权利。